

# 198

SERIES

XJS · SJS  
XJV

> 64 **Accessories**  
**Accessori**

> 69 **Dimensions**  
**Dimensioni**



**Versions · Versioni**

**XJS · SJS** 2800 rpm  
N version  $\varnothing$  24 mm



**F9**

Flange for close coupling  
AR special electric motors.  
Flangia per motori elettrici  
speciali AR  
COD.1580



**XJS** 2800 rpm  
C version  $\varnothing$  24 mm



**F6**

Flange for close coupling  
B3/B14 90 frame.  
Flangia per motori elettrici  
B3/B14 Gr.90.  
COD.1581



**XJV** 3400 rpm  
E version  $\varnothing$  5/8"



**F8**

Flange for close coupling  
NEMA 56-C.  
Flangia per motori elettrici  
NEMA 56-C.  
COD.1584



**XJS 2800 rpm N version ø 24 mm**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
XJS 8.12 N	<b>20326</b>	8	2.11	120	1740	2.5	1,8	2800	5
XJS 8.15 N	<b>20327</b>	8	2.11	150	2200	3	2,2	2800	5
XJS 10.12 N	<b>20328</b>	10	2.64	120	1740	3	2,2	2800	5
XJS 10.15 N	<b>20329</b>	10	2.64	150	2200	4	3	2800	5
XJS 11.09 N	<b>20330</b>	11	2.90	90	1300	2.5	1,8	2800	5
XJS 11.11 N	<b>20331</b>	11	2.90	110	1600	3	2,2	2800	5
XJS 11.14 N	<b>20332</b>	11	2.90	140	2000	4	3	2800	5

**SJS 2800 rpm N version ø 24 mm**

SJS 8.17 N	<b>20835</b>	8	2.11	170	2500	3.5	2,6	2800	5
SJS 10.17 N	<b>20836</b>	10	2.64	170	2500	4.5	3,3	2800	5
SJS 11.17 N	<b>20837</b>	11	2.90	170	2500	5	3,5	2800	5

**XJS 2800 rpm C version ø 24 mm**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
XJS 8.12 C	<b>20371</b>	8	2.11	120	1740	2.5	1,8	2800	5
XJS 8.15 C	<b>20484</b>	8	2.11	150	2200	3	2,2	2800	5
XJS 10.12 C	<b>20372</b>	10	2.64	120	1740	3	2,2	2800	5
XJS 10.15 C	<b>20441</b>	10	2.64	150	2200	4	3	2800	5
XJS 11.09 C	<b>20485</b>	11	2.90	90	1300	2.5	1,8	2800	5
XJS 11.11 C	<b>20373</b>	11	2.90	110	1600	3	2,2	2800	5
XJS 11.14 C	<b>20442</b>	11	2.90	140	2000	4	3	2800	5

**XJV 3400 rpm E version ø 5/8"**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
XJV 2 G15 E	<b>20374</b>	7,6	2	100	1450	2	1,5	3400	5
XJV 2.5 G15 E	<b>20375</b>	9,5	2.5	100	1450	2.5	1,8	3400	5
XJV 3 G20 E	<b>20376</b>	11,4	3	140	2000	4	3	3400	5

# 198 SERIES

SJV  
XJW-E  
XJW · SJW

> 64 **Accessories**  
**Accessori**

> 69 **Dimensions**  
**Dimensioni**



Versions · Versioni

**SJV** 3400 rpm  
D version + F7  $\varnothing$  3/4"



**XJW-E** 3400 rpm  
D version + F27  $\varnothing$  7/8"



**XJW · SJW** 3400 rpm  
D version + F27  $\varnothing$  7/8"



**SJV 3400 rpm D version + F7 ø 3/4"**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
SJV 2 G25 D+F7	<b>21663</b>	7,6	2	170	2500	3.5	2,6	3400	4,7
SJV 2.5 G25 D+F7	<b>21664</b>	9,5	2.5	170	2500	4.5	3,3	3400	4,7
SJV 3 G25 D+F7	<b>21665</b>	11,4	3	170	2500	5	3,5	3400	4,7
SJV 3 G27 D+F7	<b>21666</b>	11,4	3	186	2700	5.5	4	3400	4,7
SJV 3.5 G25 D+F7	<b>21667</b>	13,2	3.5	170	2500	6	4,4	3400	4,7

**XJW-E 3400 rpm D version + F27 ø 7/8"**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
XJW-E 2 G22 D+F27	<b>21627</b>	7,6	2	150	2200	3	2,2	3400	4,6
XJW-E 2.5 G22 D+F27	<b>21628</b>	9,5	2.5	150	2200	3.7	2,8	3400	4,6
XJW-E 3 G22 D+F27	<b>21629</b>	11,4	3	150	2200	4.5	3,4	3400	4,6

**XJW 3400 rpm D version + F27 ø 7/8"**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
XJW 2 G22 D+F27	<b>21414</b>	7,6	2	150	2200	3	2,2	3400	4,8
XJW 2.5 G22 D+F27	<b>21415</b>	9,5	2.5	150	2200	3.7	2,8	3400	4,8
XJW 3 G22 D+F27	<b>21416</b>	11,4	3	150	2200	4.5	3,4	3400	4,8

**SJW 3400 rpm D version + F27 ø 7/8"**

Pump type Tipo pompa	Code Codice	Output Portata		Pressure Pressione		Power Potenza		RPM N° giri/1'	Peso Weight Kg
		l/min	gpm	bar	psi	hp	kw		
SJW 2 G25 D+F27	<b>21417</b>	7,6	2	170	2500	3.5	2,6	3400	4,8
SJW 2.5 G25 D+F27	<b>21418</b>	9,5	2.5	170	2500	4.5	3,3	3400	4,8
SJW 3 G25 D+F27	<b>21419</b>	11,4	3	170	2500	5	3,5	3400	4,8