



**ANNOVI
REVERBERI**
The Power of Experience

ANNOVI REVERBERI S.p.A.
Via M. L. King, 3 - 41100 Modena (Italy)
Tel. (+39) 059.414.411 - Fax (+39) 059.253.505
E - Mail: industria@annovireverberi.it

Regulating valves
Soupapes de régulation
Regelungsventile
Válvulas de regulación
Valvole di regolazione
GYMATIC 3/A




TECHNICAL DATA / DONNEES TECHNIQUES / TECHNISCHE ANGABEN
CARACTERISTICAS TECNICAS / CARATTERISTICHE TECNICHE

REGULATING VALVES SOUPAPES DE REGULATION REGELUNGSVENTILE VALVULAS DE REGULACION VALVOLE DI REGOLAZIONE	CAPACITY DEBIT LEISTUNG CAUDAL PORTATA l/min	PRESSURE PRESSION DRUCK PRESION PRESSIONE bar	INLET	OUTLET
GYMATIC 3/A, + ID, IDR for XM, RK series (Cod. 20077)	11 (ø 1,8)	250		
GYMATIC 3/A, + ID, IDR for XM, RK series (Cod. 20078)	13÷18 (ø 2,1)	250		
GYMATIC 3/A, + ID, IDR for XM, RK series (Cod. 20079)	21 (ø 2,3)	250		
GYMATIC 3/A, + ID, IDR for XM, RK series (Cod. 20396)	11 (ø 1,8)	250		
GYMATIC 3/A, + ID, IDR for XM, RK series (Cod. 20397)	13÷18 (ø 2,1)	250		
GYMATIC 3/A, + ID, IDR for XM, RK series (Cod. 20398)	21 (ø 2,3)	250		



ATTENTION:
ATTENZIONE:
ACHTUNG:
ATENCIÓN:
ATTENZIONE:

- This manual must be read before beginning installation of the unit.
- Ce livret doit être lu avant d'installer et d'employer le produit.
- Das vorliegende Handbuch ist vor der Installation und dem Gebrauch des Produkts aufmerksam zu lesen.
- Este manual debe ser leído antes de proceder a la instalación y uso del producto.
- Il presente libretto va letto prima di procedere all'installazione ed uso del prodotto.



cod. 40050_Gymatic_3A

GYMATIC 3/A



Pos.	Cod. Part n°	Denominazione	Description	Q.tà Q.ty	Note Vedi / See
1	1560580	Tappo manopola	Knob plug	1	
2	180030	Vite TCEI M 8x20	Screw	1	
3	1660210	Dado M 8	Nut	1	
4	1560400	Manopola	Handle	1	
5	1080070	Spina	Pin	1	
6	1560420	Vite di regolazione	Adjusting screw	1	
7	1560410	Guida molla	Spring guide	1	
8	1560440	Piattello	PLate	1	
9	1560350	Molla	Spring	1	
10	1080610	Piattello molla	Spring plate	1	
11	1080660	Spina	Pin	1	
12	1080540	Pistone superiore	Upper piston	1	
13	391000	OR Ø 9,13x2,62	O-Ring	1	
14	1080640	Anello antiestrusione	Back-up ring	1	
15	1560150	OR Ø 5,94x3,53	O-Ring	1	
16	1560100	Otturatore	Jet	1	
17	1560140	Molla	Spring	1	
18	180101	OR Ø 17,5x2	O-Ring	1	
19	880581	Tappo	Plug	2	Optional
20	820510	OR Ø 10,82x1,78	O-Ring	2	Optional
21	1560020	Corpo valvola	Valve housing	1	
22	1080550	Anello antiestrusione	Back-up ring	2	
23	480480	OR Ø 4,48x1,78	O-Ring	2	
25	1560320	Pistone inferiore	Lower piston	1	
26	880270	OR Ø 17,17x1,78	O-Ring	1	
27	1080831	Nipples by-pass	By-pass adaptor	1	
29	1560510	Controdado	Nut	1	■ ▲
30	1560500	Raccordo 3/8" G	Fitting 3/8" G	1	Ø 1,8 ■ ▲
	1560530	Raccordo 3/8" G	Fitting 3/8" G	1	Ø 2,1 ■ ▲
	1560540	Raccordo 3/8" G	Fitting 3/8" G	1	Ø 2,3 ■ ▲
31	1560520	Molla	Spring	1	■ ▲
32	1250280	Sfera	Ball	1	■ ▲
33	480480	OR Ø 4,48x1,78	O-Ring	1	■ ▲
34	1560490	Portagomma	Hose tail	1	■
35	1560110	Nipples 3/8" G	Adaptor 3/8" G	1	● Ott./Brass
	1560111	Nipples 3/8" G	Adaptor 3/8" G	1	● Inox/Steel
36	1560650	Portagomma	Hose tail	1	▲
37	800560	OR Ø 8,73x1,78	O-Ring	1	▲
38	480560	OR Ø 6,75x1,78	O-Ring	1	▲
39	1560670	Manopola reg.det.	Detergent reg. knob	1	▲
40	1560660	Anello	Ring	1	▲
41	1080390	Controdado 3/8" G	Nut	1	

Pos.	Cod. Part n°	Denominazione	Description	Q.tà Q.ty	Note Vedi / See
42	740290	OR Ø 14x1,78	O-Ring	1	

KIT RICAMBI - PART KITS

F=KIT 2610 OR O-Rings							
Pos.	Q.ty	Pos.	Q.ty	Pos.	Q.ty	Pos.	Q.ty
13	1	33	1				
15	1	42	1				
18	1						
22	2						
23	2						
26	1						

Pos.	Q.ty	Pos.	Q.ty	Pos.	Q.ty	Pos.	Q.ty

SIMBOLOGIA - SYMBOLS

- Per / For GYMATIC 3/A MAX 250 bar
- Per / For GYMATIC 3/A + ID MAX 250 bar
- ▲ Per / For GYMATIC 3/A + IDR MAX 250 bar

DIMENSIONS / DIMENSIONES / ABMESSUNGEN / DIMENSIONES / DIMENSIONI